



DuBois Electric storage Battery Company

Effective 4-1-2013

Quality Since 1919

Part Number	CCA	RC	Voltage	Length	Width	Height	Core Unit Value	Battery Weight
12 Volt Automotive								
24/34-550		90	12	10 3/4	6 7/8	8	1	33.5
24/34-690	690	110	12	10 3/4	6 7/8	8	1	36.5
24/34-800	800	90	12	10 3/4	6 7/8	8	1	38.5
24-500	500	70	12	10 3/4	6 3/4	9	1	32
24-650	650	90	12	10 3/4	6 3/4	9	1	35.5
24-800	800	120	12	10 3/4	6 3/4	9	1	40
24F-500	500	70	12	10 3/4	6 3/4	9	1	23
24F-650	650	90	12	10 3/4	6 3/4	9	1	25.5
24F-800	800	120	12	10 3/4	6 3/4	9	1	40
25-550	550	90	12	9 3/4	8 7/8	8 7/8	1	33.5
26-525	525	60	12	8 7/8	6 3/4	8	1	29.5
26R-525	525	60	12	8 7/8	6 3/4	8	1	29.5
27-700	700	120	12	12	6 7/8	9	1	47
27F-700	700	120	12	12	6 7/8	9	1	47
35-550	550	90	12	9 3/4	8 7/8	8 7/8	1	33.5
36R-650	650	130	12	10 1/4	7 1/4	8	1	42
45-475	475	67	12	9 3/8	5 1/2	9	1	30.5
50-600	600	108	12	13 3/8	5 3/8	10	1	43
51-500	500	70	12	9 3/8	5	8 3/4	1	28
51R-500	500	70	12	9 3/8	5	8 3/4	1	28
55-525	525	75	12	8 3/4	6	8 1/2	1	29.5
58-500	500	65	12	10	7 1/4	7	1	29
58-580	580	85	12	10	7 1/4	7	1	31.5
58R-580	580	85	12	10	7 1/4	6 7/8	1	31.5
59-590	590	100	12	10	7 2/3	7 3/4	1	35
64-650	650	115	12	11 3/4	6 1/4	8 7/8	1	42
65-700	700	130	12	12	7 3/8	7 5/8	1	41
65-880	880	150	12	12	7 3/8	7 5/8	1	45.5
70-500	540	60	12	8 3/4	7	7 1/8	1	27
75-500	500	70	12	9 3/4	7	7 1/4	1	28.5
75-650	650	90	12	9 3/4	7	7 1/4	1	33
75-720	720	100	12	9 3/4	7	7 1/4	1	34.5
78-550	550	90	12	10 3/4	6 7/8	7 3/4	1	33.5

78-690	690	110	12	10 3/4	6 7/8	7 3/4	1	36.5
78-850	850	115	12	10 3/4	6 7/8	7 3/4	1	41
79-880	880	140	12	11 3/4	6 7/8	7 3/4	1	43
85-630	630	100	12	9	6 7/8	8 1/8	1	31
86-630	630	85	12	9	6 7/8	7 3/4	1	32
100-770	770	115	12	10 3/4	6 7/8	7 3/4	1	41
101-675	675	110	12	10 1/4	6 1/8	6 3/4	1	35.7
75DT-525	500	80	12	9 3/8	7	8	1	32
75DT-720	720	100	12	9 3/8	7	8	1	34.5
78DT-525	525	80	12	10 1/4	7	7 7/8	1	33.5
78DT-690	690	110	12	10 1/4	7	7 7/8	1	36.5
78DT-875	875	120	12	10 1/4	7	7 7/8	1	41
40R-650	650	110	12	11	6 7/8	7	1	37
41-675	675	110	12	11 1/4	6 7/8	7	1	38
42-500	500	70	12	9 1/2	6 7/8	7	1	29
47/90-600	600	90	12	9 1/2	6 7/8	7 1/2	1	33.5
48/91-700	700	120	12	11	6 7/8	7	1	36.5
49/93-875	875	185	12	15	6 7/8	7	1	46.5
92-650	650	130	12	12 1/2	6 7/8	7	1	37
94R-770	770	133	12	12 4/9	7	7 1/2	1	45
95R-800	800	190	12	15 1/2	7	7 1/2	1.5	64.5
96R-600	600	95	12	9 5/8	6 7/8	7 1/2	1	35
97R-600	600	95	12	9 4/7	7	7 1/2	1	36.5
121R-540	540	80	12	8 1/4	7	8 1/8	1	29.5
124R-670	670	80	12	10 1/4	6 7/8	8 3/8	1	38
151R-330	330	55	12	7 1/4	4 15/16	8 3/4	1	19
MIATA	320	45	12	8 3/4	5 1/8	7 1/4	0.5	25
Part Number	CCA	RC	Voltage	Length	Width	Height	Core Unit Value	Battery Weight